

RESPIRABLE CRYSTALLINE SILICA

WORKPLACE EXPOSURE IS PREVENTABLE



smarter permanent formwork.™


WHAT IS CRYSTALLINE SILICA?

Crystalline Silica is everywhere. It is found in naturally in stone, rocks, sand, gravel and clay.

WHAT IS RESPIRABLE CRYSTALLINE SILICA DUST?

Respirable crystalline silica is dust in materials and products containing silica. It is released when mechanically treated (e.g. cutting, sawing, abrading such as rasping, scraping, grinding down, chasing or crushing). This dust is of concern due to its size as it gets caught deep in your lungs and can cause long term damage.

CSR has conducted tests which have determined the amount of Crystalline silica that may become respirable size particles when drilling or cutting fibre cement sheets.



IF YOU USE THE CORRECT EQUIPMENT FIBRE CEMENT IS SAFE TO USE

CSR has made the following requirements

<p>Cut Outdoors *</p>	<p>The ventilation outdoors is greater than indoors, and should reduce exposure</p>	
<p>Use-Tool Dust Extraction</p>	<p>Use on-tool dust extraction when using power tools to drill and cut Fibre Cement, with a vacuum that contains a HEPA M Class Filter</p>	
<p>Correct Equipment</p>	<p>Use a plunge saw with a specifically designed Fibre Cement blade</p>	
<p>Use a Respirator</p>	<p>Use a half face P1 or P2 respirator, it is essential that respirators are fit tested and workers are cleanly shaven to obtain a good seal</p>	
<p>Clean Up</p>	<p>When completing your work vacuum with a HEPA M Class Filter, rather than a broom as sweeping creates more dust</p>	

Independent testing was conducted by Safe Environments Pty Limited to EN 689 and ISO 16258-1 (NATA accreditation 17139).



Independent testing conducted June 2021

The activity of cutting fibre cement sheets has been assessed and is considered low risk when people are trained in the task, equipment is used and maintained to manufacturer requirements and all controls as indicated are correctly in place.

Regular monitoring of people conducting this activity is highly recommended .

Disclaimer. It is the responsibility of the user to review and confirm applied controls meet exposure standards.

afsformwork.com.au | csr.com.au



NON-Hazardous, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Cemintel® Fibre Cement

Synonyms

Texture Base Sheet
CeminSeal Wallboard
Cladding Sheet
Eaves Lining Sheet
Soffitline
Compressed Sheet
Commercial ExpressPanel
Ceramic Tile Underlay
Smooth and Woodgrain Plank
Headland Weatherboard
Endeavour Weatherboard
Scarborough Weatherboard
Commercial Rendaline
Barestone Original
Barestone Ash
Barestone Lunar
Barestone Graphite
Balmoral Weatherboard
Cemintel Trims
Edge Cladding
Edge Bond 75V
Edge Oxford 150V
Edge York 300V
Edge Crown 400V
Constructafloor
Aspect Cladding
Mosaic
SimpleLine
Cavity Battens
Rigid Air Barrier

Recommended use: Used as external cladding (sheets, planks and weatherboards), cavity battens, internal lining including wet areas, bracing sheets, lining eaves and as compressed sheeting for flooring, decks and underlay for tiles. Compressed sheets may be also used as building facades.

Supplier: CSR Building Products Ltd.
ABN: 55 008 631 356
Street Address: Triniti 3, Level 5, 39 Delhi Road
North Ryde NSW 2113
Australia
Telephone: +61 2 9235 8000 (or 1800 807 668 within Australia)
Facsimile: 1300 369 448 (Bus Hrs, Mon-Fri, 8am-5pm, AEST)

Emergency Telephone number: +61 2 9372 5819

2. HAZARDS IDENTIFICATION

Based on available information, this material is not classified as hazardous according to criteria of Safe Work Australia.

The fine dust in/on the supplied product may include respirable crystalline silica. Cutting, breaking, drilling, sawing, grinding and finishing may generate dust which is **Hazardous**. Recommendations on Exposure Controls/Personal Protection (see Section 8 below) should be followed.

Poison Schedule: Not Applicable

DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Calcium silicate hydrate	1344-95-2	<60 % (w/w)
Crystalline Silica (Sand, Quartz)	14808-60-7	20 - 55 % (w/w)
Cellulose (from wood pulp)	9004-34-6	<15 % (w/w)
Water	7732-18-5	<15 % (w/w)
Other non hazardous ingredients (fillers, pigments, acrylic sealers and surface coatings)		<10 % (w/w)
		100%

Note: The respirable crystalline silica (quartz) content (if any) is less than 0.1%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact: If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

PPE for First Aiders: Wear safety shoes, overalls, gloves. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Non-combustible material.

Fire fighting further advice: Not applicable.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Dust is best cleaned up by wet sweeping and/or vacuuming to avoid making dust airborne. Wetting down before sweeping up dust may be a useful control measure. Bag waste materials.

LARGE SPILLS

Collect and dispose of large pieces. Dust is best cleaned up by wet sweeping and/or vacuuming to avoid making dust airborne. Wetting down before sweeping up dust may be a useful control measure. Bag waste materials.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

7. HANDLING AND STORAGE

Handling: Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of dust.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for spills.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Calcium silicate	-	10	-	-	-
Cellulose (paper fibre)	-	10	-	-	-
Crystalline Silica - Quartz (respirable dust)	-	0.05	-	-	-

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Keep exposures to dust as low as practicable. If power tools are used, they should be fitted with an efficient and well maintained on tool dust extraction device with a HEPA M class filter. Use a plunge saw with a specifically designed fibre cement blade.

Work in the open air and within external openings (such as doors and windows in buildings) is recommended. Local mechanical ventilation/extraction may be required to control airborne dust levels. Unpowered hand tools generate less dust when cutting or sanding. If generated dust cannot be avoided follow personal protection recommendations. Use a vacuum fitted with a HEPA M class filter instead of sweeping when cleaning dust generated from fibre cement panels.

Special Consideration for Repair and/or Maintenance of Contaminated Equipment: Where possible vacuum or wash down all gear, equipment or mobile plant prior to maintenance and repair work. If compressed air cleaning cannot be avoided, recommendations on Exposure Control and Personal Protection should be followed.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, RESPIRATOR.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

When handling fibre cement, the use of a respirator is not required. When using power tools for cutting, drilling and sanding, personal respiratory protection must be used to reduce exposure to the level of airborne respirable crystalline silica.

A suitable P1 or P2 particulate respirator used in accordance with AS/NZS 1715 and AS/NZS 1716 may be sufficient for many situations, but where high levels of dust are encountered, more efficient cartridge-type or powered respirators or supplied air helmets or suits may be necessary. Use only respirators that bear the Australian Standards Mark and are fitted and maintained correctly and kept in clean storage when not in use.

Wear safety shoes, overalls, gloves. Available information suggests that gloves made from leather should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of dust. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Flat sheets or mouldings, which may have a tinted or primed finish
Colour: Grey
Odour: Odourless

Solubility: Insoluble in water
Specific Gravity: 1.3 – 1.7
Relative Vapour Density (air=1): N App
Vapour Pressure (20 °C): N App
Flash Point (°C): N App
Flammability Limits (%): Non flammable
Autoignition Temperature (°C): N App

Safety Data Sheet

CEMINTEL®

Melting Point/Range (°C):	N App
Boiling Point/Range (°C):	N App
pH:	N App
Viscosity:	N App
Total VOC (g/Litre):	N App

(Typical values only - consult specification sheet)
N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: Stable

Conditions to avoid: Dust generation

Incompatible materials: Strong acids

Hazardous decomposition products: None

Hazardous reactions: None

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin may result in irritation.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: May be an eye irritant. Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

Acute toxicity

Inhalation: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): LC50 > 5 mg/L

Skin contact: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

Ingestion: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >2,000 mg/Kg bw

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

Crystalline Silica: Long term occupational over-exposure or prolonged breathing-in (or inhalation) of crystalline silica dust at levels above the TWA carries the risk of causing serious and irreversible lung disease, including bronchitis, and silicosis (scarring of the lung), including acute and/or accelerated silicosis. It may also increase the risk of other irreversible and serious disorders including scleroderma (a disease affecting the skin, joints, blood vessels and internal organs) and other auto-immune disorders.

Specific Toxic Effects: Inhalation of dust, including crystalline silica dust, is considered by medical authorities to increase the risk of lung disease due to tobacco smoking.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

Long-term aquatic hazard: This material has been classified as non-hazardous. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log K_{ow} < 4.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
Basel Convention (Hazardous Waste)
International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

- All components of this product are listed on or exempt from the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Reason for issue: Revised

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd on behalf of its client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.