

# Introducing rediwall® 200 Curve Panel.

Adding to our unique interlocking panel system, we're bringing RW200 Curve Panels – for a fast alternative to traditional curved wall solutions.



BEST PRACTICE PVC  
In accordance with the  
GBCA PVC guideline  
**GECA** ✓  
CLAIM AUTHENTICATED



## Why AFS RW200 curves?



### Easy to design with tight radius and length options

Available for the RW200 profile, in 3m and 3.6m panel heights, with a 15-degree segment panels to create tight curved walls down to as small as 0.5-metre radius.



### Compliant

Rediwall® is CodeMark certified to the National Construction Code (NCC), and meets the relevant requirements for structural, load bearing reinforced concrete walls designed in accordance with the (AS3600-2018) Concrete Structures Code and up to FRL 240/240/240.



### Integrated system

Seamless integration into the RW200 interlocking panel system allowing for total wall design flexibility.



### Fast solution

Delivered to site ready to install, there's no cutting or drilling required, resulting in less on site preparation.

## Curve panel specs.



Radius 0.5m



Diameter 1.0m



Sizing RW200



15-degree angle



### Want more information?

Scan the QR code or visit [afsformwork.com.au/rediwall-curve-panel](https://afsformwork.com.au/rediwall-curve-panel) to find out more about this product.

**CSR**